



3290

AIR COOLED CONDENSER COATING

- ✓ Easy To Use
- ✓ Does Not Affect Heat Transfer
- ✓ Prevents Rust & Corrosion
- ✓ Ideal For Salt Air Environments

FIN SAVER AEROSOL is a specially formulated coating containing acrylic polymers and anticorrosion agents designed to protect painted or unpainted metals from rust and corrosion. FIN SAVER seals and protects aluminum, copper, brass, bronze, chrome, galvanized metal, titanium and stainless steel. It is ideally suited for use on air cooled condensers located in corrosive environments such as paper mills, chemical plants, airports, adjacent to freeways and salt air areas.

DANGER: Keep out of reach of children. Read label and SDS before use. extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. May cause damage to central nervous system through prolonged or repeated exposure via inhalation. Suspected of damaging the unborn child via inhalation. Causes skin irritation. Causes serious eye irritation.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/spray. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands and face thoroughly after handling. Wear protective gloves. Wear eye protection. If exposed or concerned: Get medical attention. FIRST AID: IF SWALLOWED: Immediately call a poison center or a doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, and national regulations. ⚠ **WARNING:** This product can expose you to Toluene which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Contains [CAS]: Toluene [108-88-3], Propane [74-98-6] and Isobutane [75-28-5].



DIRECTIONS FOR USE: Clean condenser thoroughly, allow to dry completely. Shake can vigorously for at least 15 seconds. Protect surrounding areas from over-spray. Spray with sweeping motions 6-10 inches from surface to be treated. Always turn open end of nozzle away from you. Several thin coats are better than one thick coat. Dries dust free in 30 minutes. Can be handled after one hour. Apply only when temperature is above 40° F and equipment to be treated is dry.



**ISO 9001:2015
CERTIFIED**

North American Research Corp.

519 Huffines Blvd., Lewisville, TX 75056

800.527.7520 | 972.492.1800

Fax: 972.394.6755

Web: NarcoChem.com

info@narcochem.com