



5408

## LEAK DETECTOR

- ✓ Fluorescent, High Viscosity
- ✓ Clings to all Surfaces
- ✓ Freeze-Proof to 0°F

**WARNING:** COMBUSTIBLE LIQUID. FOR PROFESSIONAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.

**WARNING:** Combustible liquid. Causes serious eye irritation. May cause drowsiness or dizziness. KEEP OUT OF REACH OF CHILDREN. Read entire label & Safety Data Sheet before use.

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Wear protective gloves/eye and face protection. Wash thoroughly after handling. Avoid breathing fume/vapors. Use only in a well-ventilated area.

In case of fire: Use foam, carbon dioxide, dry powder or water mist to extinguish.

**FIRST AID:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Contains [CAS]: Isopropyl alcohol [67-63-0].



### DIRECTIONS FOR USE:

To detect leaks, use dauber cap to apply liberally around joints of pressurized gas systems. Large leaks bubble up immediately. Slow, small leaks bubble up within a few seconds.



**ISO 9001:2015  
CERTIFIED**

#### North American Research Corp.

519 Huffines Blvd., Lewisville, TX 75056

800.527.7520 | 972.492.1800

Fax: 972.394.6755

Web: NarcoChem.com

info@narcochem.com