



2008-XX

2008-01, 2008-05, 2008-30, 2008-55

INHIBITS RUST AND CORROSION IN OPEN RECIRCULATING WATER SYSTEMS DURING WINTER SHUT DOWN

- ✓ **Biodegradable**
- ✓ **Environmentally safe**

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER PRESSURE. SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS. FOR PROFESSIONAL USE ONLY.

DANGER: May be fatal if swallowed and enters airways. FOR PROFESSIONAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.



FIRST AID: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation develops or persists: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

Most important symptoms/effects: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis.

Contains [CAS]: Distillates (petroleum), hydrotreated light [64742-47-8].



**ISO 9001:2015
CERTIFIED**

North American Research Corp.

519 Huffines Blvd., Lewisville, TX 75056

800.527.7520 | 972.492.1800

Fax: 972.394.6755

Web: NarcoChem.com

info@narcochem.com



DIRECTIONS FOR USE: Add 5 gallons of FILMEX for each 1000 gallons of water in the system. Slowly pour about ¼ of the required amount into the sump ahead of the circulating pump suction. Wait for 10 minutes and add the balance of the amount of FILMEX required. Circulate normally for 3 to 4 hours, then drain system.

The amount of water in the system can be estimated by multiplying the sump length by width by depth in feet and multiplying by 10.

FILMEX is biodegradable and environmentally safe.