



3663-XX

3663-01, 3663-05, 3663-30, 3663-55

NON-ACID FOAMING AIR COOLED CONDENSER CLEANER/BRIGHTENER

- ✓ **Foams Out Stubborn Deposits from Air Cooled Condensers**
- ✓ **Very Effective on Heavy Grease Accumulations**
- ✓ **USDA Accepted**

DANGER: MAY BE CORROSIVE TO METALS. CAUSES SERIOUS SKIN BURNS AND EYE DAMAGE. FOR PROFESSIONAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONS.

DANGER: May be corrosive to metals. Causes severe skin burns and eye damage.

Keep in original container. Do not breathe mist/vapors/spray. Wash face, hands, and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

FIRST AID: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/Doctor.

Store locked up. Dispose of contents and container in accordance with all local, regional, and national regulations.

Contains [CAS]: Potassium hydroxide [1310-58-3], sodium hydroxide [1310-73-2], sodium silicate [1344-09-8].



ISO 9001:2015
CERTIFIED

North American Research Corp.

519 Huffines Blvd., Lewisville, TX 75056
800.527.7520 | 972.492.1800

Fax: 972.394.6755

Web: NarcoChem.com

info@narcochem.com



NARFOAM is specially formulated for the cleaning and brightening of air conditioning condenser coils. It is non-acidic, non-flammable and contains no toxic petroleum or chlorinated solvents. The surfactants used in NARFOAM are biodegradable.

DIRECTIONS FOR USE:

TIP: Cleaning action is accelerated if condenser coil is still warm from use.

1. Read entire label & **Safety Data Sheet** before use.
2. Disconnect all power before working on equipment.
3. Protect surrounding area from over-spray.
4. Using a suitable low-pressure sprayer, dilute NARFOAM with water according to dilution rates below.
5. Always spray downwind with a coarse spray to avoid misting. Spray between fins using horizontal motion, working from the bottom up.
6. Wait 3 to 4 minutes until foam begins to subside and rinse completely with large amounts of water.
7. Flush sprayer completely with water after use.

DO NOT USE ON INDOOR COILS. USE ONLY OUTDOORS.

DILUTION RATE:	ADD 1 PART CLEANER TO:
HEAVY DUTY CLEANING	2-3 PARTS WATER
MODERATE DUTY CLEANING	4-6 PARTS WATER
LIGHT DUTY CLEANING	UP TO 10 PARTS WATER